

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Endereço	GlasStress Ltd. Glass stress measurement equipment 21/1 Akadeemia Str. 12618 Tallinn
Telefone	00372 655 5531
Fax	00372 655 5532
INTERNET	www.glasstress.com
Empregados	5
Ano de fundação	2003
Taxa de exportação	100 %

PESSOAS PARA CONTACTAR

Contact 1. Sr. Johan Anton
CEO
Phone: 00372 655 5531
Fax: 00372 655 5532

PRODUTOS / MÁQUINAS

Initially, GlasStress Ltd supplied instruments for laboratory use. Developments now concentrates on higher volume lower cost stress analysis equipment that may also be implemented as quality control instruments at the production line. The personnel of GlasStress Ltd has 50 years of experience in measuring stress in glass articles.

At the moment, the most sellable machine is scattered light polariscopes SCALP-05. GlasStress Ltd offers also automatic transmission polariscope AP-07 and scattered light polariscopes SCALP-04.

Scattered light polariscopes are meant for through-the-thickness stress measurement. SCALP-04 is suitable for stress measurement in architectural glass panels and automotive glazing. SCALP-05 is meant for stress measurement in automotive and solar glasses, also in chemically tempered glasses. Both polariscopes are computer controlled. Handling of the polariscopes is extremely simple: just place the the device on the glass panel to be measured and press slightly the button on the left side of the device. After ten seconds the stress profile through the panel thickness is shown on the screen of the laptop.

Polariscope AP-07 is a computer controlled device designed for automatic stress measurement in solid and hollow axisymmetric glass products (drinking glasses, bottles, neck tubes of CRT bulbs, lamps, optical fibre preforms, etc.). It permits also edge stress measurement in glass plates and automotive glazing, thickness stress measurement in strips cut out from glass plates, and measurement of stress at edge corners. Photoelastic measurements are completely automatic and take from 2 to 15 seconds. After that stress distribution in any section of the test object can be displayed on the screen. Integrated photoelasticity algorithms are used for stress calculation from the measurement data. The polariscope can be used for stress measurement near the production line. Its handling does not need any knowledge about photoelasticity or stress analysis.

HISTÓRIA DE EMPRESA

GlasStress Ltd is a manufacturer of internal residual stress measurement equipment for glass products. GlasStress Ltd offers automatic transmission polariscopes AP for container, tableware, lighting industries and scattered light polariscopes SCALP for automotive, architectural, solar industries.

Company Profile of **GlasStress Ltd.**

A service of glassglobal.com, an affiliate of glassglobal group.

O material impresso endereço que você é autor e pertence à empresa ou ao seu terceiro Marketing Agency, e todos os direitos reservados. Qualquer usuário que acessa esse material poderá fazê-lo apenas para seu próprio uso pessoal, bem como a utilização desse material é de risco exclusivo do Utilizador. A redistribuição ou exploração comercial de material, tais endereço é expressamente proibida. Sempre que tal material endereço é fornecido por um terceiro, cada utilizador concorda em observar e estar vinculado aos termos específicos de utilização aplicáveis a material notícia. Glass Global não representa nem endossa a precisão ou confiabilidade de qualquer informação contida em qualquer endereço ou sites externos referidos no presente impresso. www.glassglobal.com - O Portal Internacional para a Indústria do Vidro - Ogis GmbH