

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Endereço **Shandong Yaohua Glass Co.,Ltd**
No.7 Kuaiyuan Road
Wangsheren Town
250101 Jinan City

PRODUTOS / MÁQUINAS

Products:

New low E insulation glass

insulation glass
laminated glass
tempered glass

You can combination of these. E.g. tempered laminated and insulation glass

curved or bent tempered glass
glass curtain wall
Bulletproof glass
Art glass

Introduce for product

Insulation Glass

Insulation glass solutions from yaohua glass consist of two or three panes of glass that are hermetically sealed. Insulating units reduce heat gained and lost between interior and exterior spaces, contributing to outstanding overall energy efficiency.

Thickness:3mm-15mm

Specification:

Max:2440mmx6000mm

Min: 200mmx300mm

Tempered Glass

Tempered glass offers outstanding safety protection, as it breaks into small, pebble-like pieces. Tempered glasses are ideal for any area where high traffic and human contact may pose safety concerns.

Thickness:4mm-19mm

Specification:

Max:3000mmx8000mm

Laminated Glass

Laminated products consist of two or more glass lites bonded together by a plastic interlayer of polyvinyl butyral (PVB) under heat and pressure. The resulting laminated product—which is visually indistinguishable from monolithic glass

Laminated products provide excellent personal protection when used as safety glazings in commercial buildings of all types. While the surface of laminated products may be broken, the resulting glass shards stay bonded to the PVB plastic interlayer and typically stays on the window or door frame—making them a perfect safety solution when glass be breakaged.

Thickness:3mm-19mm

Specification:

Max:2440x7000mm

Low-E Insulation Glass

The low-E insulation glass can save energy and protect climate through the reduction of carbon dioxide emissions and increased efficiency of components that consume energy – such as reducing the energy consumption of buildings.

The low-E insulation glass gives windows outstanding thermal insulation, while at the same time the warming infrared radiation can enter the building and create solar heating.

Thickness:3-15mm

Specification:

Max:3660x2440mm

Min: 200x300mm

Hot bent Glass

For various areas of application with high technical and aesthetic requirements. For more creativity in order to satisfy building industry.

Thickness:3-19mm

Specification:

Max: 3500x2500mm

Max bent: 650mm

Bent tempered glass

Tempering of curved or bent glass for added strength,safety or both.

There has been an increasing demand for curved or bent tempered glass in buildings and other commercial applications. More curved or bent glass to be used exteriorly in building facades and interiorly in many unique applications in order to create more efficient and dramatic effects.

Thickness:3-19mm

Specifcation:

Max:3000mmx5000mm

R=1500mm

Company Profile of Shandong Yaohua Glass Co.,Ltd

A service of glasssglobal.com, an affiliate of glasssglobal group.

O material impresso endereço que você é autor e pertence à empresa ou ao seu terceiro Marketing Agency, e todos os direitos reservados. Qualquer usuário que acesse esse material poderá fazê-lo apenas para seu próprio uso pessoal, bem como a utilização desse material é de risco exclusivo do Utilizador. A redistribuição ou exploração comercial de material, tais endereço é expressamente proibida. Sempre que tal material endereço é fornecido por um terceiro, cada utilizador concorda em observar e estar vinculado aos termos específicos de utilização aplicáveis a material notícia. Glass Global não representa nem endossa a precisão ou confiabilidade de qualquer informação contida em qualquer endereço ou sites externos referidos no presente impresso. www.glasssglobal.com - O Portal Internacional para a Indústria do Vidro - Ogis GmbH