

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Endereço

China Guangdong PVD Metallizer Co.

Guangdong Zhenhua Technology

Yungui road, Zhaoqing Avenue West Block. Zhaoqing, Guangdong, China

526000 Zhaoqing

PRODUTOS / MÁQUINAS

Horizontal continuous production line for VIP vacuum insulated panel

Our company produces various models of production line for vacuum insulated panel (VIP) as per customers technical requirements, enabling to meet their actual demands. Model XF2000-V/S production line for VIP/STP vacuum insulated panel with structure of the world's first horizontal continuous production line, with features of stable good quality and high efficiency, is an exclusive one in the world and it can achieve the capacity of 8 pieces per minute of VIP/STP panels sized 600X400X65mm. (Specifications of VIP/STP panels can be made as per customers specific demands and requirements. Maximum VIP/STP panel size 1500mmX2000mmX55mm.). Vacuum insulated panel (referred to as VIP in short form) is a newly developed efficient insulation material in recent years with very low thermal conductivity. Its structure consists of 3 parts as insulation material in the core, gas collecting material called Getter and membrane walls used to prevent air from entering the panel called Barrier. It is made by the principle of vacuum insulation through powerful evacuation with vacuum pumps to realize the maximum internal vacuum pressure to prevent heat conduction, which can effectively avoid the three ways as conduction, convection and radiation to achieve insulation and energy-saving purposes. Vacuum insulated panel, one of the vacuum insulation material with low thermal conductivity and excellent properties of thermal insulation and environmental protection, is currently the world's most efficient insulation products. It is a perfect substitute for traditional insulation material and products, extensively used in refrigerators, freezers, water heaters, refrigerated containers, building materials for facades or exterior walls. Its thermal conductivity can be achieved less than 1.5mw/m.k.

Company Profile of **China Guangdong PVD Metallizer Co.**

A service of glasssglobal.com, an affiliate of glasssglobal group.

O material impresso endereço que você é autor e pertence à empresa ou ao seu terceiro Marketing Agency, e todos os direitos reservados. Qualquer usuário que acessa esse material poderá fazê-lo apenas para seu próprio uso pessoal, bem como a utilização desse material é de risco exclusivo do Utilizador. A redistribuição ou exploração comercial de material, tais endereço é expressamente proibida. Sempre que tal material endereço é fornecido por um terceiro, cada utilizador concorda em observar e estar vinculado aos termos específicos de utilização aplicáveis a material notícia. Glass Global não representa nem endossa a precisão ou confiabilidade de qualquer informação contida em qualquer endereço ou sites externos referidos no presente impresso. www.glasssglobal.com - O Portal Internacional para a Indústria do Vidro - Ogis GmbH