

This website uses cookies to improve the user's experience during working with our network and to provide users with dedicated services and functions. By further use you agree with that.OKDetails

Endereço	Sphere Hotwork 36/FF, Maruti Complex, Opp. 390002 Vadodara
----------	---

PRODUTOS / MÁQUINAS

REFRACTORY DRYOUT

It is very much important that proper dryout of refractories should be undertaken as water is the common solvent for mixing of mortars, rams, castables, cements used for installation. This water which is hydraulically bonded through chemical interactions, between various refractories after installation needs to be driven out from the lining or else can cause a severe crack by trapping steam in the lining which shall ultimately give way to the entire castable lining. To ensure optimum refractory performance it is imperative that all moisture is removed thoroughly and uniformly during the course of heat-up and prior to the plant being subjected to onstream production.

General description of the procedure of the dry-out of a refractory lining:

For the dry-out of a refractory lining external High velocity burners are used. These external burners are fired with light weight oil/Gas and will be installed in openings like manholes or doors.

One burner unit exists of the mobile burner with the Extended Nozzle, the Combustion fan, regulation flap for the combustion air, the connecting air duct and the regulation unit. The fans are sucking the ambient air and compress it up to max. 60 mbar. This air used for combustion of the burner.

The burner itself consists of the combustion chamber in which the fuel oil and compressed air/Gas will be mixed with the combustion air and ignited and the steel part (extended nozzle, manufactured of heat resistant steel) which will lead the flue gases. These extended nozzle could be straight or with an angle and the end so that the flue gas could be led to a desired direction and critical parts close to the burner will not be "touched" directly by the flue gases.

The air duct is used for the compressed ambient air to the burner.. The required temperature of the outgoing flue gases will be controlled and achieved by controlling fuel oil by our specialists who are on site continuously.

The flue gas temperature is controlled manually by controlling oil flow by valve of the oil train to achieve required temperature as per the heating schedule.

The maximum temperature reading of all the thermocouple placed in equipment will be considered as target temperature.

Cement Industry

- PreHeater & Cyclones
- Rotary Kilns & Inter Coolers
- Coolers
- Rawmills
- Cement Mills

Power Industry

- C.F.B.C. Boilers
- Seal Port
- ASH Cooler & Cyclones
- Waste Heat Boilers
- Combustions Beds

Ducts
Coal Collector
Kiln

Steel Industry

Hot Blast stove / Furnace
Metallic Pre-Heater reactor
Runners & Laddles
Blast Furnace Dryout
Hot Blast main
Bustle Pipe Dryout
Cokeovens

Aluminium Industry

Furnace
Cyclones
Rotary Lilns & Inter Coolers
Calcliner

Copper Industry

Copper Smelters
Anode Furnaces & Laddlers
Chimney's

Fertilizer & Chemical Industry

Lime Kiln
Secondary Reformer
R.G. Boilers
Reactor
Heat Exchanger & Reformer
Incinerator

Petro Chemicals

Sulphur Furnace
FCCU / SRU / BBU
Reactor
Sulphur Condenser
Main Combustion Chambers / Fired Heaters / Stacks
Primary Reformer
Secondary Reformer
Vacun Heaters
Incinerator

Non Ferrous metal

Aluminium Holding Furnaces
Aluminium Melting Furnaces
Induction Furnaces
Tilting Furnaces

Company Profile of **Sphere Hotwork**

A service of glasssglobal.com, an affiliate of glasssglobal group.

O material impresso endereço que você é autor e pertence à empresa ou ao seu terceiro Marketing Agency, e todos os direitos reservados. Qualquer usuário que acessa esse material poderá fazê-lo apenas para seu próprio uso pessoal, bem como a utilização desse material é de risco exclusivo do Utilizador. A redistribuição ou exploração comercial de material, tais endereço é expressamente proibida. Sempre que tal material endereço é fornecido por um terceiro, cada utilizador concorda em observar e estar vinculado aos

termos específicos de utilização aplicáveis a material notícia. Glass Global não representa nem endossa a precisão ou confiabilidade de qualquer informação contida em qualquer endereço ou sites externos referidos no presente impresso. www.glasssglobal.com - O Portal Internacional para a Indústria do Vidro - Ogis GmbH